

PRICE QUOTATION FORM

Note: Please fill-out the Price Quotation Form completely with the corresponding unit price of each item and the total price of the required quantities. Otherwise, the said quotation shall not be considered by the DOJ Bids and Awards Committee

Date: _____

Assistant Secretary **MARGARET V. CASTILLO-PADILLA**
 Chairperson, DOJ Bids and Awards Committee
 Room 112, Ground Floor, De las Alas Hall, DOJ Compound
 Padre Faura Street, Ermita, Manila

Madam:

After having carefully read the terms and conditions in the Request for Quotation for the Project: **Supply and Delivery of CAMERA with LENS, PROFESSIONAL CAMCORDER with TRIPOD, LAPEL MICROPHONES, and VIDEO LIGHTING EQUIPMENT**, hereunder is our proposal/price quotations for the following item/s:

Quantity	Unit	Description	Unit Price	Total Price
1	unit	<p style="text-align: center;">CAMERA with LENS</p> Camera – 20.9 million megapixel <ul style="list-style-type: none"> • Sensor Size: 23.5mm x 15.6 mm • Storage: SD / SDHC / SDXC • ISO Sensitivity: ISO 100 – 51,200 • 8 fps Continuous Shooting with • Extended Buffer Capacity • Cinematic Versatility and • 4K UHD Video Recording 		
1	unit	<p style="text-align: center;">Lens (Camera Compatible)</p> <ul style="list-style-type: none"> • Image Circle: APS-C • Type: Wide Frame • Focal Length: 16mm • APS Equivalent: 1.5x: 24mm; 2.0x : 32mm • MAX : MIN Aperture: f/1.4 – f/16 • Diaphragm Blades: 9 (rounded) 		
1	unit	<p style="text-align: center;">PROFESSIONAL CAMCORDER with TRIPOD</p> Camcorder with Tripod <ul style="list-style-type: none"> • Supply Voltage DC 7.2 V (when the battery is used) • DC 7.9 V (when the AC adaptor is used) • Power Consumption 15.0 W (when the LCD monitor is used) • Operating Temperature 0 °C to 40 °C (32 °F to 104 °F) • Operating Humidity 10% to 80% 		

- (no condensation)
- Weight Approx. 2.5 kg (5.5 lb) excluding battery and accessories
- Dimensions (W x H x D) 18.0 cm x 19.5 cm x 43.8 cm excluding battery, accessories and protrusions
- Camera Section Pickup Devices 1/3-type progressive, 2.2-megapixel, 3MOS sensor
- Effective Pixels 1920 (H)×1080 (V)
- Lens Optical image stabilizer lens, 22x motorized zoom, F1.6 – 3.2 (f=0.39 cm – 8.6 cm), 3.5 cm conversion: 2.8 cm – 61.6 cm (16:9)
- Filter Diameter 7.2 cm
- Optical System Prism color separation
- ND filter OFF, 1/4, 1/16, 1/64
- Minimum Shooting Distance Approx. 1 m
- Hood Large-sized lens hood with wide angle of view
- Shutter Opening Angle 3 degrees to 359.5 degrees' in 0.5 degree increments
- Sensitivity 59.94 Hz mode: (at 2000 lx, 3200 K, 89.9% reflection) F7 (1080/59.94i, P.A.P FILTER: TYPE2) F10 (1080/59.94i, P.A.P FILTER: TYPE1)
- 50 Hz mode: (at 2000 lx, 3200 K, 89.9% reflection) F8 (1080/50i, P.A.P FILTER: TYPE2) F11 (1080/50i, P.A.P FILTER: TYPE1)
- Minimum Illumination 0.2 lx (F1.6, Gain +30 dB, shutter speed 1/30 sec., P.A.P FILTER: TYPE1)
- Digital Zoom ×2, ×5, ×10

LAPEL MICROPHONES

- | | | |
|---|------|--|
| 2 | unit | Digital Frequency Modulate Frequency <ul style="list-style-type: none"> • Range: UHF 660-669.5MHz • Preset Frequency: 20 (auto paring) • Frequency Response: 75Hz-18kHz ±3dB • Max. Devlation Range: ±50kHz (with level limiting) • T.H.D.: <1.0% at 1kHz • S/N: >98dB • Working Range: Up to 50m |
|---|------|--|

VIDEO LIGHTING EQUIPMENT

- | | | |
|---|-----|---|
| 1 | set | Photography Video Shooting Lighting <ul style="list-style-type: none"> • Dimmable Bi-color LED Light: • With white and yellow LED long lasting bulbs, adjustable color temperature 3200K-5600K, adjustable brightness |
|---|-----|---|

0%-100%; U-mount bracket enables the photographers to adjust the lighting angle according to the shooting environment.

- Adjustable Light Stand with Solid locking capabilities ensure the safety of your lighting equipment when in use.
- Premium Material and Multi-use:
Made of excellent quality aluminum Alloy.

TOTAL P

(Amount of Bid in Words) _____

The above-quoted prices are inclusive of all costs and applicable taxes.

Very truly yours,

Name and Signature of the Bidder
or Authorized Representative

Name of Company/Business

Address

Contact No. and E mail Address