

### PRICE QUOTATION FORM

Date: \_\_\_\_\_

Assistant Secretary **MARGARET V. CASTILLO-PADILLA**  
 Chairperson, DOJ Bids and Awards Committee  
 Room 112, Ground Floor, Delas Alas Hall, DOJ Compound  
 Padre Faura Street, Ermita, Manila

Madam:

After having carefully read the terms and conditions in the Request for Quotation for the Project: **Purchase of various other machinery and equipment**, hereunder is our proposal/price quotations for the following item/s:

Quantity	Unit	Description	Unit Price	Total Price
1	unit	<b><i>Fiber Glass Extension Ladder</i></b> D-Shaped Rungs Patented quick latch rung lock system Steel swivel safety shoes with metal shield Mar-resistant rail end caps Outside slide guides Direct rung-rail connection Non-conductive side rails for working around electricity <b>Materials:</b> Fiberglass <b>Size:</b> 24ft <b>Load Capacity:</b> 225lbs <b>Size Product:</b> 41L x 15W x 380H cm		
1	unit	<b><i>Aluminum Folding Ladder</i></b> 5 steps x 4 fold (19ft) High strength aluminum profiles With special locking device Pedal profile for the tubes, stable non-slip		
1	unit	<b><i>Laser Range Finder</i></b> <b>Power type:</b> Rechargeable <b>Size:</b> 125 x 54 x 27 mm <b>Measurement accuracy:</b> +/-2mm <b>Laser level:</b> 635nm class II <b>Measure range:</b> 100 meters		
1	unit	<b><i>Electric Circuit Tester</i></b> 600V Cat III safety design specifications 50% of the display range, bright white backlight Over voltage indicator Frequency and temperature measurement Voltage, resistance, current, capacitance Input terminal of the AC and DC current measurement value of 10A Diode test, data retention		

Quantity Price	Unit	Description	Unit Price	Total
1	unit	<p><b>Mechanical Measuring Wheel</b>            Measure 10,000 meters            Increment of 10 cm            Patent protected wrist design            High traction flat PU tire mounted onto rim            Firm and solid kickstand  <b>Wheel Diameter:</b> 318.5mm  <b>Wheel Circumference:</b> 100cm</p>		
1	unit	<p><b>Telephone Line Test Handset</b>            High-impedance monitor for uninterrupted data, conversations or signaling            DTMF tone/pulse switchable dial pad to test signals            3-position volume control for up 12dB of gain            Polarity indicator            Last number redial (3-digit max)            10 number memory storage            Includes cloth covered cord equipped with anchored strain relief            Modular RJ11 plug            Two 5-way test clips and spade connector cord</p>		
2	unit	<p><b>Push Cart/Platform Truck – 300Kg.</b>            4-ball bearing braked wheels for easy and safe steering            Tubing and flat form made of tough steel and for added durability            Strong, rigid steel handle for secure maneuvering of loads            Scroll down  <b>Open dimensions:</b> 91 x 61 x 85cm  <b>Folded dimension:</b> 91 x 61 x 28cm  <b>Steel base plate:</b> 91 x 61cm  <b>Ball bearing wheels:</b> 12.5cm PP+TPR  <b>Weight:</b> 14.5kg</p>		

**TOTAL P**

(Amount of Bid in Words) \_\_\_\_\_

\_\_\_\_\_

The above-quoted prices are inclusive of all costs and applicable taxes.

Very truly yours,

---

Name and Signature of the Bidder  
or Authorized Representative

---

Name of Company/Business

---

Address

---

Contact No. and E mail Address